

## IN THE CLAIMS:

This listing of the claims replaces all prior versions and listings of the claims in this application.

The text of all pending claims (including any withdrawn claims) is set forth below. Canceled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with strikethrough. The status of each claim is indicated with one of (Original), (Currently amended), (Canceled), (Withdrawn), (Previously presented), (New), and (Not entered).

Please AMEND claims 1, 8, and 9 and ADD new claim 10 in accordance with the following:

1. (Currently amended) A computer-readable medium usable with an apparatus comprising a buffer, the computer-readable medium having recorded thereon:
  - audio video (AV) data;
  - a markup document ~~which was provided to be preloaded into the buffer of the apparatus~~ to enable the apparatus to reproduce the AV data in an interactive mode selected by a user of the apparatus; and
  - control information ~~which was provided to enable the apparatus to~~ identify buffering state information of the markup document to be preloaded into the buffer of the apparatus, the buffering state information being used by the apparatus in reproducing the AV data in the interactive mode selected by the user.
2. (Previously presented) The computer-readable medium of claim 1, wherein the control information includes an application program interface (API) that generates a report signal used to identify a buffering state of the markup document.
3. (Previously presented) The computer-readable medium of claim 1, wherein the control information includes an [obj].isCached(URL, resType) API that generates a report signal, where the URL is a parameter indicating a file path of the markup document and the resType is a parameter indicating an attribute of the markup document.

4. (Previously presented) The computer-readable medium of claim 1, wherein the control information includes an API that returns a value of 0 in response to preloading of the markup document being successful, a value of 1 in response to the preloading of the markup document being failed, and a value of 2 in response to the preloading of the markup document still being conducted.

5. (Previously presented) The computer-readable medium of claim 1, wherein the control information includes an API that generates a fetch signal used to issue a command to preload the markup document.

6. (Previously presented) The computer-readable medium of claim 5, wherein the API returns a response indicating whether the command to preload the markup document has been successfully transmitted using the fetch signal.

7. (Previously presented) The computer-readable medium of claim 1, wherein the control information includes an API that is used to determine whether preloading of the markup document is completed.

8. (Currently amended) The computer-readable medium of claim 1, wherein the AV data is ~~AV data that was selected~~ selectable by a the user to be viewed by the user while ~~being the~~ AV data is reproduced in the interactive mode selected by the user.

9. (Currently amended) The computer-readable medium of claim 1, wherein the interactive mode selected by the user is an interactive mode ~~that was selected by a~~ in which the user who will view views the AV data ~~in the interactive mode~~.

10. (New) The computer-readable medium of claim 1, wherein:  
the interactive mode is a mode in which the AV data is displayed in a display window defined by the markup document;  
the apparatus is selectively operable in the interactive mode in which the AV data is displayed in the display window defined by the markup document, and a non-interactive video

mode in which the AV data is displayed in the same manner as AV data recorded on a standard DVD; and

the user of the apparatus selects between the interactive mode and the non-interactive video mode.